

1. Product- And Company	Issue Date	28.04.2009	
1.1 Trade Name	FS-4020D		
1.2 Company	<i>Kyoceramita Europe B.V., Otto-Hahn Strasse 12, D-40670 Meerbusch</i>		
1.3 Phone	<i>+49-(0)2159-928-922</i>		
2. Safety Approvals	Safety: EN 60950 /60825 EMC: EN 55022 / 55024 / 61000		
3. Environment Approvals	<i>Meet the criteria of RAL UZ 122 (Blue Angel) and RoHS</i>		
4. Power Consumption	Maximum: 1061 W Print Mode: 667 W Ready Mode (Eco Fuser Off): 79 W Ready Mode (Eco Fuser On): 9.9 W Sleep Mode: 6.4 W		
5. Installation Notes	<i>The machine should be placed more than 10 cm from the wall with a minimum of left 30 cm/right 30 cm/front 100cm space for operation and maintenance. Sufficient ventilation should be provided. The machine should not be placed in a dusty room or where ammonia gas is in use.</i>		
6. Room Humidity	15% – 80 %		
7. Room Temperature	10.0 °C – 32.5 °C		
8. Noise Level	Print Mode: 69.2 dB(A) LW ^{Ad} Stand-by: 41.6 dB(A) LW ^{Ad} Sleep Mode: N.A.		
9. Light Source	N.A.		
10. Emissions	TVOC Print Mode: TVOC Stand-by: Benzene: Styrene: Ozone: Fine Dust:	4.400 mg/h 0.008 mg/h 0.014 mg/h 0.062 mg/h Unmeasureable low 1.400 mg/h	RAL UZ 122 RAL UZ 122 RAL UZ 122 RAL UZ 122 RAL UZ 122 RAL UZ 122
11. Others			