

<b>1. Product- And Company</b>	<b>Issue Date</b>		17.02.2010	
<b>1.1 Trade Name</b>	<b>TASKalfa-552ci</b>			
<b>1.2 Company</b>	<i>Kyoceramita Europe B.V., Otto-Hahn Strasse 12, D-40670 Meerbusch</i>			
<b>1.3 Phone</b>	<i>+49-(0)2159-928-922</i>			
<b>2. Safety Approvals</b>	<i>Safety 73/23/EEC EMC 89/336/EEC</i>			
<b>3. Environment Approvals</b>	<i>EU RoHS</i>			
<b>4. Power Consumption</b>	<i>Maximum: 1656W Print Mode (monochrome): 1330W Print Mode (colour): 1360W Ready Mode: 230 W Sleep Mode: 20 W</i>			
<b>5. Installation Notes</b>	<i>The machine should be placed more than 40 cm from the wall with a minimum of left 30 cm/right 30 cm/front 100cm space for operation and maintenance. Sufficient ventilation should be provided. The machine should not be placed in a dusty room or where ammonia gas is in use.</i>			
<b>6. Room Humidity</b>	<i>20 % – 80 %</i>			
<b>7. Room Temperature</b>	<i>10.0 °C – 32.5 °C</i>			
<b>8. Noise Level</b>	<i>Printing: 70.7 dB(A) Lwad RAL UZ 122 Stand-by: 40.9 dB(A) Lwa RAL UZ 122 Sleep modus: not measurable</i>			
<b>9. Light Source</b>	<i>Exposure Drum: Semiconductor Laser</i>			
<b>10. Emissions</b>	<i>Ozone: Styrene: Benzene: TVOC: Dust:</i>	<i>B/W: 0.100 mg/h &lt;0.020 mg/h 0.030 mg/h 8.800 mg/h 2.100 mg/h</i>	<i>Colour: 0.200 mg/h &lt;0.020 mg/h 0.040 mg/h 14.300mg/h &lt;0.140 mg/h</i>	<i>RAL UZ 122</i>
<b>11. Others</b>				